



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product name A08100
MSDS name PRIMER - N40 L
CAS number Mixture
Generic description Solvent Based Primer
Manufacturer Bostik, Inc.
211 Boston Street
Middleton, MA 01949 USA
24 hour emergency assistance Telephone: 1-800-227-0332
General assistance Telephone: 1-978-777-0100
MSDS assistance Telephone: 1-414-607-1347

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Isopropyl alcohol	67-63-0	60 - 100

3. HAZARDS IDENTIFICATION

Emergency overview Liquid and vapors are flammable. Contact may cause skin and eye irritation. Mist may cause nose and throat irritation. Ingestion will cause nausea, vomiting, pain, upset stomach, and diarrhea.

Potential health effects

Skin This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Eyes Liquid or vapors may irritate the eyes. Prolonged or repeated contact may worsen irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May lead to permanent damage if not treated promptly.

Inhalation This product may cause irritation to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Ingestion This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Lungs, skin and eyes.

Signs and symptoms of overexposure Signs and symptoms of overexposure to this product include headache, irritation of upper respiratory tract, asthmatic symptoms, chest tightness, breathing difficulty, coughing, eye irritation, skin irritation, diarrhea.

4. FIRST AID MEASURES

First aid

Skin Remove contaminated clothing to prevent further skin exposure and dispose of properly. In situations involving considerable skin contact, place the contaminated person in a deluge shower for at least 15 minutes. For minor exposures, wash thoroughly with soap and clean water. Get medical attention if irritation persists.

Eye In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

Inhalation Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist.

Ingestion If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

Notes to physician This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated.

5. FIRE FIGHTING MEASURES

Extinguishing media	Use dry chemical, carbon dioxide, or foam. Use water spray on large fires. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools; this may result in frothing and increase fire intensity.
Basic fire fighting procedures	Empty containers may retain product residue including Flammable or Explosive vapors. Do not cut, drill, grind, or weld near full, partially full, or empty product containers.
Sensitivity to mechanical impact	None Known
Sensitivity to static discharge	Sparks generated by static discharge may ignite this product or its vapors. All containers and equipment must be bonded or grounded to minimize risk.
Unusual fire & explosion hazards	During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. Vapors may be heavier than air and may travel long distances along the ground before igniting back to vapor source. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water.
Fire fighting equipment/instructions	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Flash point	61 °F (16.1 °C)

6. ACCIDENTAL RELEASE MEASURES

Emergency action	Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up.
Containment	Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.
Reporting	See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

7. HANDLING & STORAGE

Handling	Keep this product from heat, sparks, or open flame. Avoid getting this material into contact with your skin and eyes. Wash hands thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, face shields, and gloves. Professionally launder contaminated clothing before re-use. Avoid breathing vapors or mists of this product. Use this product with adequate ventilation. Do not reuse the empty container.
Storage	Keep the container tightly closed and in a cool, well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. All containers must be bonded or grounded to minimize risk.
Empty container precaution	Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur. Do not heat or cut empty container with electric or gas torch.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended exposure limits. Explosion proof exhaust ventilation should be used.
Eye protection	Wear safety glasses; chemical goggles (if splashing is possible). Contact lenses should not be worn.
Skin and body protection	Impervious gloves should be used at all times when handling this product. Recommended gloves include rubber, neoprene, nitrile or viton. Use of protective coveralls and long sleeves is recommended.
Respiratory protection	Avoid breathing vapor and/or mists. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator.
General	Eyewash fountains and emergency showers should be readily available. Use good industrial hygiene practices in handling this material.

Exposure limits

ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA)

Isopropyl alcohol 67-63-0 200 ppm TWA

NIOSH - Pocket Guide - TWAs

Isopropyl alcohol 67-63-0 400 ppm TWA; 980 mg/m3 TWA

OSHA - Final PELs - Time Weighted Averages (TWAs)

Isopropyl alcohol 67-63-0 400 ppm TWA; 980 mg/m3 TWA

OSHA - Vacated PELs - TWAs

Isopropyl alcohol 67-63-0 400 ppm TWA; 980 mg/m3 TWA

9. PHYSICAL & CHEMICAL PROPERTIES

Percent volatile	0 %
pH	N/A
Density	0.796 g/cc
Odor	SOLVENT
Color	CLEAR
Physical state	Liquid
Freeze protect	No

10. STABILITY & REACTIVITY

Hazardous reactions/decomposition products	If product is burned carbon monoxide, carbon dioxide, and other unknown products may be produced.
Hazardous polymerization	Will not occur.
Conditions to avoid	Keep away from sources of ignition.
Stability	Stable under normal conditions. This product may react with strong acids, bases and oxidizing agents.

11. TOXICOLOGICAL INFORMATION

Toxicological data If any toxicological data is available, it will be listed below:

LD50

Toxicology Data - Selected LD50s and LC50s

Isopropyl alcohol 67-63-0 Inhalation LC50 Rat: 72.6 mg/L/4H; Oral LD50 Rat: 4396 mg/kg; Dermal LD50 Rat: 12800 mg/kg; Dermal LD50 Rabbit: 12800 mg/kg

Chronic effects	Chronic exposure to solvents can cause reproductive problems, reduced fertility, dryness and cracking of skin, headaches, loss of appetite and nausea.
Carcinogenicity	If this product contains any carcinogens, they will be noted below:

12. ECOLOGICAL INFORMATION

Ecotoxicological information Organic solvents produce slight to moderate toxicity to aquatic life. Insufficient data exists to evaluate the effect on plants, birds or land animals.

13. DISPOSAL CONSIDERATIONS

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Empty containers must be handled with care due to product residue. Do not heat or cut empty container with electric or gas torch.

14. TRANSPORT INFORMATION

DOT

Basic shipping requirements:

Proper shipping name Isopropanol
Hazard class 3
UN number UN1219
Packing group II

Additional information:

Special provisions IB2, T4, TP1
Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242



IATA

Basic shipping requirements:

Proper shipping name Isopropanol
Hazard class 3
UN number UN1219
Packing group II

Additional information:

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242
Labels required 3



IMDG

Basic shipping requirements:

Proper shipping name Isopropanol
Hazard class 3
UN number UN1219
Packing group II

Additional information:

Packaging exceptions 150
Labels required 3



15. REGULATORY INFORMATION

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA - Section 313 - Emission Reporting

Isopropyl alcohol 67-63-0 1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)

State regulations If this product contains any ingredients listed under California Proposition 65, they will be noted below:

California - Proposition 65 - Developmental Toxicity

Ethyl Alcohol 64-17-5 developmental toxicity, initial date 10/1/87 (when in alcoholic beverages)

International regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

HMIS Ratings
Health: 2
Flammability: 3
Physical hazard: 0
Personal protection: X

SARA 311/312 HAZARD CATEGORIES

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No
Controlled

WHMIS status

WHMIS labeling



WHMIS classification

B2 - Flammable/Combustible
D2B - Other Toxic Effects-TOXIC

16. OTHER INFORMATION

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date

12/01/2006

Prepared by

Michael Simon

Supersedes

11/30/2006