



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

| | |
|-------------------------------------|--|
| Product name | D-1001 Ceramic Mastic Series |
| Product name(s) covered | See Section 16 for Product Names Covered. |
| MSDS name | D-1001 Ceramic Mastic Product Series |
| CAS number | Mixture |
| Product use | Tile Setting |
| Generic description | Acrylic Mastic |
| Manufacturer | Bostik, Inc. 211 Boston Street Middleton, MA 01949 USA |
| 24 hour emergency assistance | Telephone: 1-800-227-0332 |
| General assistance | Telephone: 1-978-777-0100 |
| MSDS assistance | Telephone: 1-414-607-1347 |

2. COMPOSITION / INFORMATION ON INGREDIENTS

| Component(s) | CAS # | Percent |
|---------------------|--------------|----------------|
| Ethylene glycol | 107-21-1 | 1 - 5 |
| Stoddard solvent | 8052-41-3 | 1 - 5 |

3. HAZARDS IDENTIFICATION

| | |
|---------------------------------|---|
| Emergency overview | Extended contact with this material may cause irritation to the skin, eyes, and mucous membranes. Primary Routes of Exposure: eyes, skin, and inhalation. |
| Potential health effects | |
| Skin | Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. |
| Eyes | May cause irritation with temporary redness with stinging and tearing. |
| Inhalation | Inhalation: Inhalation of mist and/or vapor may cause respiratory irritation, dizziness, nausea, or headache. |
| Ingestion | This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. |

4. FIRST AID MEASURES

| | |
|---------------------------|---|
| First aid | |
| Skin | Remove contaminated clothing to prevent further skin exposure and dispose of properly. In situations involving considerable skin contact, place the contaminated person in a deluge shower for at least 15 minutes. For minor exposures, wash thoroughly with soap and clean water. Get medical attention if irritation persists. |
| Eye | Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Do not attempt to neutralize with chemical agents. Get medical attention immediately. Get medical attention or advice. |
| Inhalation | Remove to fresh air. Get medical attention immediately for a large dose exposure or if cough or other symptoms develop. |
| Ingestion | If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to a victim who is unconscious or is having convulsions. |
| Notes to physician | If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. |

5. FIRE FIGHTING MEASURES

| | |
|---|---|
| Hazardous combustion products | Decomposition can produce hazardous chemicals. Carbon monoxide, carbon dioxide, acetic acid, vinyl acetate, and other unknown products may be produced during combustion. |
| Extinguishing media | Use dry chemical, carbon dioxide, or foam. |
| Sensitivity to mechanical impact | None Known |
| Sensitivity to static discharge | None Known |
| Unusual fire & explosion hazards | During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. Vapors may be heavier than air and may travel long distances along the ground before igniting back to vapor source. High temperatures can cause sealed containers to rupture due to a buildup of internal pressures. Cool with water. |
| Fire fighting equipment/instructions | Firefighters should wear full protective clothing including self contained breathing apparatus. |
| Flash point | > 200 °F (> 93.3 °C) |

6. ACCIDENTAL RELEASE MEASURES

| | |
|-------------------------|--|
| Emergency action | Appropriate safety measures and protective equipment should be used. See Section 8. Do not discharge to lakes, streams, ponds, or sewers. Dispose of in compliance with local, state, and federal regulations. |
| Containment | Scrape up spilled material and place into appropriate containers for proper disposal. |
| Reporting | See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements. |

7. HANDLING & STORAGE

| | |
|-----------------------------------|---|
| Handling | Wash hands thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, face shields, and gloves. Professionally launder contaminated clothing before re-use. |
| Storage | Store in a cool, dry, well-ventilated area away from heat, ignition sources and direct sunlight. |
| Empty container precaution | Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| | |
|---|--|
| Engineering controls | Use local exhaust ventilation when vapors, mists, or dusts are being generated. Suitable respiratory equipment should be used when insufficient ventilation or operational procedures demand it. |
| Eye protection | Wear goggles or safety glasses with side shields. Contact lenses should not be worn. |
| Skin and body protection | Wear rubber boots and apron, protective clothing, and impervious gloves to minimize skin exposure. |
| Respiratory protection | None required where adequate ventilation conditions exist. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. |
| General | Eyewash fountains and emergency showers should be readily available. |
| Exposure limits | |
| ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA) | |
| Stoddard solvent | 8052-41-3 <u>100 ppm TWA</u> |
| NIOSH - Pocket Guide - TWAs | |
| Stoddard solvent | 8052-41-3 <u>350 mg/m3 TWA</u> |
| U.S. - OSHA - Final PELs - Time Weighted Averages (TWAs) | |
| Stoddard solvent | 8052-41-3 <u>500 ppm TWA; 2900 mg/m3 TWA</u> |
| U.S. - OSHA - Vacated PELs - Ceilings | |
| Ethylene glycol | 107-21-1 <u>50 ppm Ceiling; 125 mg/m3 Ceiling</u> |
| U.S. - OSHA - Vacated PELs - TWAs | |
| Stoddard solvent | 8052-41-3 <u>100 ppm TWA; 525 mg/m3 TWA</u> |

9. PHYSICAL & CHEMICAL PROPERTIES

| | |
|----------------|------------|
| Density | 1.525 g/cc |
| Odor | Mild |

Color White
Physical state Paste
Freeze protect Yes

10. STABILITY & REACTIVITY

Hazardous reactions/decomposition products If product is burned carbon monoxide, carbon dioxide, acetic acid, vinyl acetate, and other unknown products may be produced. Additionally, depending on conditions, some aliphatic aldehydes and carboxylic acids may be formed.

Hazardous polymerization Will not occur.

Conditions to avoid Excessive heat over 200°C or cold under 10°C. Avoid amines, strong bases, alcohols and metallic hydrides.

Stability Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

Toxicological data If any toxicological data is available, it will be listed below:

LD50

Toxicology Data - Selected LD50s and LC50s

Ethylene glycol 107-21-1 Oral LD50 Rat: 4000 mg/kg; Dermal LD50 Rabbit: 9530 µL/kg

12. ECOLOGICAL INFORMATION

Ecotoxicological information Organic solvents produce slight to moderate toxicity to aquatic life.

13. DISPOSAL CONSIDERATIONS

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of in compliance with all local, state, and federal regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local, and state laws.

14. TRANSPORT INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

All components are on the U.S. EPA TSCA Inventory List.

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Ethylene glycol 107-21-1 5000 lb final RQ; 2270 kg final RQ

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Ethylene glycol 107-21-1 1.0 % de minimis concentration

U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification

Xylenes (o-, m-, p- isomers) 1330-20-7 Section 4

State regulations

If this product contains any ingredients listed under California Proposition 65, they will be noted below:

U.S. - California - Proposition 65 - Carcinogens List

Acetaldehyde 75-07-0 carcinogen, initial date 4/1/88 Trace impurity

Ethyl acrylate 140-88-5 carcinogen, initial date 7/1/89 Trace impurity

Formaldehyde 50-00-0 carcinogen, initial date 1/1/88 (gas) Trace impurity

International regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

HMIS Ratings

Health: 1
Flammability: 1
Physical hazard: 0
Personal protection: X
Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No
Controlled

SARA 311/312 HAZARD CATEGORIES**WHMIS status
WHMIS labeling****WHMIS classification**

D2B - Other Toxic Effects-TOXIC

16. OTHER INFORMATION**Product name(s) covered**

D60654 - D-1001 CERAMIC MASTIC 6X1QT
D60656 - D-1001 CERAMIC MASTIC 4X1GL
D60658 - D-1001 CERAMIC MASTIC 3.5GL

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date

10/23/2007

Prepared by

Pam Larsen

Supersedes

10/23/2007

MSDS sections updated

Handling & Storage: Storage