



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product name G00270
MSDS name SL150 SELF-LEVEL UNDERLAYMENT
Product name(s) covered See Section 16 for Product Names Covered.
CAS # Mixture
Product use Repair and Smoothing of Floors
Generic description Formulated Cement Self-Leveling Underlayment
Manufacturer Bostik, Inc.
211 Boston Street
Middleton, MA 01949 USA
24 hour emergency assistance Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887
General assistance Telephone: 1-978-777-0100
MSDS assistance Telephone: 1-414-607-1347

2. Hazards Identification

Emergency overview Exposure to dust may be irritating to eyes, nose, and throat. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of Silica dust. This product contains trace amounts of hexavalent chromium, a skin sensitizer and human carcinogen. Prolonged/repeated exposure may cause severe allergic skin reactions and/or cancer.

Potential health effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. Mechanical rubbing may increase skin irritation.

Skin contact may cause an allergic response in some individuals due to trace amounts of chromium (6+) salts. Symptoms can range from a mild rash to severe skin ulcers. Persons already sensitized to hexavalent chromium may experience symptoms after minimal exposure.

Inhalation This product contains free crystalline silica. Prolonged or repeated inhalation of crystalline silica can aggravate lung conditions and lead to silicosis, a seriously disabling and potentially fatal lung disease. Inhalation of free crystalline silica has also been linked to increased occurrence of renal disease and auto immune disorders.

Ingestion Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target organs Respiratory tract - Silica can target and damage the lungs. Some studies show an increased incidence in kidney and end-stage renal disease in individuals exposed to respirable Silica. Hexavalent chromium can cause skin sensitization and damage.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Silica, Quartz	14808-60-7	30 - 60
Portland Cement	65997-15-1	10 - 30
Calcium carbonate	1317-65-3	7 - 13
Calcium sulfate	7778-18-9	5 - 10
Gypsum (Ca(SO4).2H2O)	13397-24-5	0.5 - 1.5

Composition comments Chronic overexposure to Silica can cause chronic lung disease (Silicosis) and/or cancer. Portland Cement contains up to 10 ppm (0.001%) Hexavalent chromium, which is a skin sensitizer and carcinogen.

Parts Per Million (ppm) = 0.0001%

mg/kg = 1 ppm (0.0001%)

g/kg = 1000 ppm (0.1%)

Conversion from mg/m³ to ppm: ppm = (mg/m³ / molecular weight in grams) x 24.45

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.

Skin contact Wash affected area with mild soap and water.

Inhalation If inhaled, immediately remove the affected person to fresh air. Call a physician if symptoms develop or persist. Consult a physician after significant exposure.

Ingestion If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

Notes to physician Short-term exposure to very large amounts of respirable crystalline silica can cause serious lung inflammation and pulmonary edema, resulting in shortness of breath and low blood oxygen levels. Longer-term exposure may result in nodules of chronic inflammation and scarring in the lungs and chest lymph nodes. Symptoms of long-term exposure may resemble those of chronic obstructive pulmonary disease (COPD).

5. Fire Fighting Measures

Hazardous combustion products Non-combustible, substance itself does not burn.

Extinguishing media

Suitable extinguishing media Use any media suitable for the surrounding fires.

Basic fire fighting procedures Not a fire hazard. This material will not burn.

Fire fighting equipment/instructions Firefighters should wear full protective clothing including self contained breathing apparatus.

Dust explosion hazard None Known

Sensitivity to static discharge None Known

Flash point Non- Flammable

6. Accidental Release Measures

Emergency action Isolate area. Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Avoid contact with skin and eyes.

Environmental precautions Prevent further leakage or spillage if safe to do so.

Containment procedures Contain the discharged material. Sweep up material and place in appropriate disposal container. Use sweeping compound or other cleaning aids to pick up residues. Wash down area thoroughly with water. Use appropriate personal protective equipment as necessary.

Reporting See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

Personal precautions Avoid dust formation.

7. Handling and Storage

Handling Avoid breathing dusts from this material. Avoid getting this material into contact with your skin and eyes.

Storage Keep the container tightly closed and in a cool, well-ventilated place.

Empty container precaution Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls / Personal Protection

Engineering controls Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

Personal protective equipment

Respiratory protection None required where adequate ventilation conditions exist. Special applications may necessitate the use of more stringent respiratory protection equipment.

General Eye wash fountain and emergency showers are recommended.

9. Physical & Chemical Properties

Target solids 100 %
Density 2.6 g/cc
Odor Mild
Color Gray
Physical state Powder
Freeze protect No

10. Chemical Stability & Reactivity Information

Stability Stable under normal conditions.

11. Toxicological Information

Chronic effects Chronic overexposure to Silica has been associated with the development of chronic lung disease (Silicosis) and cancer. Hexavalent chromium can cause skin sensitization, dermatitis, and cancer. Individuals already sensitized to Hexavalent chromium can have an adverse reaction to even small exposures.

Carcinogenicity If this product contains any carcinogens, they will be noted below:

12. Ecological Information

Ecotoxicological information No data available for this product.

13. Disposal Considerations

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14. Transport Information

DOT

Not regulated as hazardous goods.

IATA

Not regulated as hazardous goods.


IMDG

Not regulated as hazardous goods.

15. Regulatory Information

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200

The product(s) covered by this M(SDS) do not include any of the 15 substances in the Candidate List of Substances of Very High Concern (SVHC) for authorization published by ECHA on October 28, 2008 above a concentration of 0.1% weight by weight (w/w).

Federal regulations	All components are on the U.S. EPA TSCA Inventory List.
State regulations	If this product contains any ingredients listed under California Proposition 65, they will be noted below:
US - California Proposition 65 - CRT: Listed date/Carcinogenic substance	
Silica, Quartz	14808-60-7 Listed: October 1, 1988 Carcinogenic.
US - California Proposition 65 - CRT: Listed date/Developmental toxin	
Lithium carbonate	554-13-2 Listed: January 1, 1991 Developmental toxin.
International regulations	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.
HMIS Ratings	Health: 1* Flammability: 1 Physical hazard: 0 Personal protection: X
SARA 311/312 HAZARD CATEGORIES	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
WHMIS status	Controlled
WHMIS labeling	
	
WHMIS classification	D2A - Other Toxic Effects-VERY TOXIC
16. Other Information	
Disclaimer	The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.
Further information	Any characters following an individual item number are just designations for the various types of packaging that are available for this product. For example, a product "G12345-XX" is item number "G12345" with a packaging designation of "XX". These characters do not indicate a different product nor a different regulatory, health, safety and/or environmental status. This document covers the item numbers listed above for all of their packaging types.
Issue date	11/09/2009
Prepared by	Pam Larsen
Supercedes	08/29/2008
This data sheet contains changes from the previous version in section(s):	This document has undergone significant changes and should be reviewed in its entirety.