



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product name	BH Roof Flash Series
MSDS name	BH Roof Flash Series - Various Colors
Product name(s) covered	See Section 16 for Product Names Covered.
CAS #	Mixture
Product use	Polyurethane Sealant/Adhesive
Generic description	Moisture Cure Urethane
Manufacturer	Bostik, Inc. 211 Boston Street Middleton, MA 01949 USA
24 hour emergency assistance	Telephone: 1-800-227-0332
General assistance	Telephone: 1-978-777-0100
MSDS assistance	Telephone: 1-414-607-1347

2. Hazards Identification

Emergency overview	This product is irritating to the eyes and skin. Thermal decomposition/burning may produce toxic gases and fumes. Closed containers may rupture when exposed to high temperatures, or when the product has been contaminated with water. Avoid breathing hot mists and vapors. This product contains a respiratory and skin sensitizer. Causes respiratory tract irritation and may cause allergic respiratory reaction. May cause permanent respiratory damage. Product vapors are potentially irritating to skin. May cause allergic skin reaction and dermatitis.
Potential health effects	
Eyes	This product may cause irritation to the eyes. May cause temporary corneal injury. May cause temporary corneal injury and This product may cause irritation to the eyes.
Skin	Skin contact may cause irritation. Isocyanates may react with skin protein and moisture to cause itching, reddening, swelling, scaling or blistering. Individuals previously sensitized to this material may experience these symptoms from exposure to very small amounts of liquid or vapor.
Inhalation	This product may cause irritation to the respiratory system. Single large does, and/or repeated exposures, may lead to sensitization to diisocyanates or polyisocyanates (asthma or asthma-like symptoms), causing an individual to experience adverse effects at exposure levels well below exposure limits or guidelines. Symptoms may include chest tightness, wheezing, shortness of breath, coughing or asthmatic attack, and may be delayed up to several hours. Extreme asthmatic reactions can be life threatening. Once sensitized, an individual may experience adverse symptoms upon exposure to dust, cold air or other irritants. Sensitization can last several months, years or be permanent in some cases.
Ingestion	This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. May cause irritation and corrosive action in the mouth, throat and digestive tract.
Target organs	The lungs and skin may be targeted and damaged by components of this product.
Signs and symptoms	Signs and symptoms of overexposure to this product include headache, irritation of upper respiratory tract, asthmatic symptoms, chest tightness, breathing difficulty, coughing, sore throat, eye irritation, skin irritation and/or diarrhea.
Hazard statements	This product contains Methylene Diphenyl Isocyanate (MDI) which is a potential skin sensitizer and has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity. Risk to your health depends on duration and concentration of exposure.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Stoddard solvent	8052-41-3	2.5 - 10
Methylene Diphenyl Isocyanate (MDI)	101-68-8	0.1 - 1

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.

Skin contact For skin contact, wash immediately with soap and water. If irritation persists, get medical attention. For severe exposure, immediately get under a safety shower and begin rinsing.

Inhalation Remove to fresh air. Call a physician if symptoms develop or persist. Administer oxygen or artificial respiration as needed.

Ingestion If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Notes to physician Treat symptomatically and supportively. Contact Bostik to determine whether any additional information is available. Eyes: Stain for evidence of corneal injury. If cornea is burned, apply antibiotic/steroid preparation as needed. Skin: This product contains a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically.

Inhalation: This material contains a known pulmonary sensitizer. Any individual experiencing dermal or pulmonary sensitization should be removed from exposure to any diisocyanate. May aggravate existing heart conditions, particularly those with abnormal heart rhythms. If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5. Fire Fighting Measures

Hazardous combustion products Additional decomposition products include oxides of nitrogen, amines, hydrogen cyanide and isocyanate-containing compounds.

Extinguishing media

Suitable extinguishing media Use dry chemical, carbon dioxide, foam, or water spray (fog).

Fire fighting equipment/instructions Firefighters should wear NFPA compliant structural fire fighting protective equipment, including a self-contained breathing apparatus, helmet, hood, boots and gloves. Avoid contact with isocyanates. During a fire, isocyanate vapors and other irritating and highly toxic gases may be produced.

Dust explosion hazard None Known

Explosion data

Sensitivity to static discharge Not available.

Sensitivity to mechanical impact Not available.

Flash point 145 °F (62.8 °C)

6. Accidental Release Measures

Emergency action Appropriate safety measures and protective equipment should be used. See Section 8. Do not discharge to lakes, streams, ponds, or sewers. Dispose of in compliance with local, state, and federal regulations.

Spill or leak procedure Scrape up paste and place in steel drums that are in good condition. Thoroughly clean area where spill occurred.

Containment procedures Isolate spill area. Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams.

Reporting See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

7. Handling and Storage

Handling

Wash hands thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, face shields, and gloves. Professionally launder contaminated clothing before re-use. Do not breathe vapors, mists or dusts. Do not breathe fumes generated when the material is overheated or burned. Use adequate ventilation. Wear respiratory protection if the material is heated, sprayed, used in a confined space or if exposure limit is exceeded. This product can produce asthmatic sensitization. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must avoid fumes from this product. Wear appropriate protective equipment to avoid contact with skin and eyes.

Storage

Store in a cool, dry, well-ventilated area away from heat, ignition sources and direct sunlight. Water contamination should be avoided. Cool location should be 60-80 degrees F or 15-30 degrees C.

Empty container precaution

Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls / Personal Protection

Engineering controls

Use local exhaust or general ventilation where the potential exists to exceed the PEL or TLV exposure limits.

Personal protective equipment

Eye protection

Wear goggles or safety glasses with side shields.

Skin and body protection

Wear appropriate clothing to minimize skin contact with this product.

Respiratory protection

Avoid breathing vapor and/or mists. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator.

General

Eyewash fountains and emergency showers should be readily available.

Additional exposure data

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m³ & ppm

Methylene Diphenyl Isocyanate (MDI) 101-68-8 METHYLENE BISPHENYL ISOCYANATE (MDI) 0.005 PPM

Stoddard solvent 8052-41-3 STODDARD SOLVENT 100 PPM

US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Methylene Diphenyl Isocyanate (MDI) 101-68-8 METHYLENE BISPHENYL ISOCYANATE 0.2 MGM³ - 0.020 PPM 10-min

Stoddard solvent 8052-41-3 STODDARD SOLVENT 1800 MGM³ 15-min

US OSHA Table Z-1-A: Time Weighted Average (TWA): mg/m³ & ppm

Stoddard solvent 8052-41-3 STODDARD SOLVENT 525 MGM³ - 100 PPM

9. Physical & Chemical Properties

Target solids

97.1 %

Density

1.753 g/cc

Odor

Mild Solvent

Color

Various

Physical state

Paste

Freeze protect

No

VOC (Volatile Organic Compounds)

51 g/l

10. Chemical Stability & Reactivity Information

Hazardous reactions/decomposition products

Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion may include carbon dioxide, carbon monoxide, water vapor, oxides of nitrogen and a wide variety of innocuous or toxic fumes. Additional decomposition products include oxides of nitrogen, amines, hydrogen cyanide and isocyanate-containing compounds.

Hazardous polymerization Conditions to avoid

Hazardous polymerization can occur with elevated temperatures or contact with water.

Avoid Strong Acids. Avoid amines, strong bases, alcohols and metallic hydrides.

Stability

This product is stable under normal conditions but will react slightly with water to release some heat and carbon dioxide. The reaction is not violent. Carbon dioxide, carbon monoxide and in high temperature (800° F) low oxygen atmospheres such as in fire situations, hydrogen cyanide may be released.

11. Toxicological Information**Carcinogenicity**

If this product contains any carcinogens, they will be noted below: This product contains Methylene Diphenyl Isocyanate (MDI). MDI is not listed by the NTP, IARC or regulated by OSHA as a carcinogen. However, it has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity.

Local effects

Single large does, and/or repeated exposures, may lead to sensitization to diisocyanates or polyisocyanates (asthma or asthma-like symptoms), causing an individual to experience adverse effects at exposure levels well below exposure limits or guidelines. Symptoms may include chest tightness, wheezing, shortness of breath, coughing or asthmatic attack, and may be delayed up to several hours. Extreme asthmatic reactions can be life threatening. Once sensitized, an individual may experience adverse symptoms upon exposure to dust, cold air or other irritants. Sensitization can last several months, years or be permanent in some cases. Chronic exposure may cause lung damage, including fibrosis and decreased lung function, which may be permanent.

12. Ecological Information

Ecotoxicological information Organic solvents produce slight to moderate toxicity to aquatic life.

13. Disposal Considerations

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of in compliance with all local, state, and federal regulations.

14. Transport Information**DOT**

Not regulated as hazardous goods.

IATA

Not regulated as hazardous goods.

IMDG

Not regulated as hazardous goods.

15. Regulatory Information

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations All components are on the U.S. EPA TSCA Inventory List.

State regulations If this product contains any ingredients listed under California Proposition 65, they will be noted below:

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Diisodecyl Phthalate (DIDP) 68515-49-1 Listed: April 20, 2007 Developmental toxin.

International regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

All components are included on the Canadian Domestic Substances List (DSL).

HMIS Ratings

Health: 2*
Flammability: 2
Physical hazard: 0
Personal protection: X

SARA 311/312 HAZARD CATEGORIES

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No
Controlled

WHMIS status

WHMIS labeling



WHMIS classification

D2A - Other Toxic Effects-VERY TOXIC
D2B - Other Toxic Effects-TOXIC

16. Other Information

Product name(s) covered

A52315 - BH ROOF FLASH WHITE 12/10.1
A52415 - BH ROOF FLASH BLACK 12/10.1
A52516 - BH ROOF FLASH STONE 12/10.1
A66815 - BH ROOF FLASHNG BRONZE 12/10.1

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Issue date

06/24/2008

Prepared by

Pam Larsen